

Mad4Heli is proud to announce that they will be stocking the Xpert Servo range for RC helicopters in Australia. As most of you know Mad4Heli is synonymous with quality RC heli gear and Xpert servos are a perfect fit for our product line up.

There are two servo sets that will initially feature that are both high end Brushless, and feature rich solutions for both small (micro servo) and large (full size servo) RC helicopters.

# The New R1 Servo a Paradigm shift in RC Helicopter control:





### **Features**

- **Quick release cable** that allows easy and quick installation for all helicopters.
- **Brushless** motor design provides extremely high speed, top efficiency, and low power consumption.
- **4096 resolution** and SIC (Single Integrated Circuit) for the highest performance and durability.
- *Light weight* design all Aluminium case for the best thermal dissipation and durability.
- Strong Metal Gear
- Glitch-free sophisticated error correction
- High-Speed, High-precision 12-bit AD converter and CPU calculation
- Fail safe Over current protection Over temperature protection
- Start sonorant Audible start up
- Operating frequency up to 400Hz

## **SPECIFICATIONS**

HS-640 XPERT		tandard <mark>C</mark>	yclic Servo	HS-3302T-HV XPERT R1 Standard <b>Tail</b> Servo				
Dimens	Dimensions: 4		40mm x 37.80mm x 20 mm		ons: 4	40mm x 37.80mm x 20 mm		
We	72 g		Weight: 72 g					
Voltage	Speed sec/60		Torque kg-cm	Voltage	Speed sec/60		Torque kg-cm	
6.0v	0.086		21.43 kg-cm	6.0v	0.056		12.00 kg-cm	
7.4V	0.07		26.43 kg-cm	7.4V	0.045		14.80 kg-cm	
8 <b>/</b> V	8.4V 0.062		30.00 kg-cm	8.4V	0	040	16.80 kg-cm	





The ultimate in Micro Servos Currently the only Brushless Micro servos available:



### **Features**

- **Brushless** motor design provides extremely high speed, top efficiency, and low power consumption.
- **4096 resolution** and SIC (Single Integrated Circuit) for the highest performance and durability.
- *Light weight* design all Aluminum case for the best thermal dissipation and durability.
- Strong Metal Gear
- Glitch-free sophisticated error correction
- *High-Speed, High-precision* 12-bit AD converter and CPU calculation
- Fail safe Over current protection Over temperature protection
- Start sonorant Audible start up
- Operating frequency up to 400Hz

### **SPECIFICATIONS**

CM-240	01-HV	7		CM-2301T-HV						
XPERT	450c	lass Micro	SUPER	XPERT 450 class HIGH SPEED						
TORQU	E MI	ETAL Cyc	clic Servo	METAL narrow band Tail Servo						
Dimono	iona	22.15mm v	29mm x 13 mm	Dimensions: 23.15mm x 29			29mm x 13 mm			
Dimensions: 23.15mm Weight: 21 g			2911111 × 1311111	Weight:			291111 X 13 11111			
Voltage	Speed sec/60		Torque	Voltage	Speed sec/60		Torque			
6.0v	0.85		6.02 kg-cm	6.0v	0.071		3.89 kg-cm			
7.4V		0.069	7.02 kg-cm	7.4V	0.58		4.80 kg-cm			
8.4V	0.061		8.27 kg-cm	8.4V	0.051		5.45 kg-cm			